



Modelo	Capacidade Roscar	Haste ø	Mandril Indicado	D dia.	D1 dia.	D2 dia.	L1	L3	L4	L5
KWES / 1B	M 3 - M 12	3.5 - 11.3	1	32	19	19	17	25	21.5	25
KWES / 2B	M 8 - M 20	7.0 - 18.0	2	50	30	31	30	31	35.0	34
KWES / 3B	M 14 - M 33	11 - 28	3	72	48	48	44	41	55.5	45
KWES / 4B	M 22 - M 48	18 - 36	4	95	60	60	71	61	63	68

Ver tabela na pág. 142.

Código	Modelo	ø	∇	Rosca
03201	KWES / 1B	2,80	2,10	(M2,5)
01238		3,50	2,70	(M3 - M5 - 1/8")
01239		4,00	3,00	(M3,5 - M4)
01684		4,50	3,40	(M4 - M6 - 5/32" - 1/4")
02813		5,50	4,30	(3/16")
01240		6,00	4,90	(M5)
01685		6,00	4,90	(M6)
01241		6,00	4,90	(M8)
01242		7,00	5,50	(M10 - G1/8" - 1/4" - 3/8")
01243		8,00	6,20	(M8 - 5/16")
01679		9,00	7,00	(M12 - 3/8" - 1/2")
01244		10,00	8,00	(M10)
01245		11,00	9,00	(M14 - G1/4" - 9/16")
02137		KWES / 2B	6,00	4,90
02138	7,00		5,50	(M10 - G1/8" - 1/4" - 3/8")
01957	8,00		6,20	(M8 - 5/16" - 7/16)
01959	9,00		7,00	(M12 - 3/8" - 1/2")
01958	10,00		8,00	(M10)
01246	11,00		9,00	(M14 - G1/4" - 9/16")
01247	12,00		9,00	(M16 - G3/8" - 5/8")
01248	14,00		11,00	(M18 - 3/4")
01700	16,00		12,00	(M20 - G1/2")
01701	18,00		14,50	(M22 - G5/8" - 7/8")
01702	18,00	14,50	(M24 - G5/8" - 7/8")	
02357	KWES / 3B	11,00	9,00	(M14 - G1/4" - 9/16")
02358		12,00	9,00	(M16 - G3/8" - 5/8")
02359		14,00	11,00	(M18 - 3/4")
01950		16,00	12,00	(M20 - G1/2")
01951		18,00	14,50	(M22 - G5/8" - 7/8")
02828		18,00	14,50	(M24 - G5/8" - 7/8")
01952		20,00	16,00	(M27 - G3/4" - 1")
01953		22,00	18,00	(M30 - G7/8" - 1.1/8")
01954		25,00	20,00	(M33 - G1" - 1.1/4")
01955		28,00	22,00	(M36 - G1.1/8" - 1.3/8")
04542	KWES / 4B	18,00	14,50	(M22 - G5/8" - 7/8")
04543		18,00	14,50	(M24 - G5/8" - 7/8")
04544		20,00	16,00	(M27 - G3/4" - 1")
04545		22,00	18,00	(M30 - G7/8" - 1.1/8")
04546		25,00	20,00	(M33 - G1 - 1.1/4")
04547		28,00	22,00	(M36 - G1.1/8" - 1.3/8")
04548		32,00	24,00	(M39 - 1.1/2")
02935		32,00	24,00	(M42 - 1.5/8")
04549		36,00	29,00	(M45 - G1.3/8" - 1.3/4")
04550		36,00	29,00	(M48 - G1.1/2" - 1.7/8")